

10/732,843  
END5007USNPAmendments to the Claims

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A biopsy device comprising:  
a hollow biopsy needle having a tissue receiving port;  
a hollow cutter advancable within the biopsy needle to sever tissue received within the tissue receiving port, wherein the cutter has a plurality of holes spaced from the distal end of the cutter, and wherein the holes are positioned for providing vacuum axially through the cutter when multiple tissue samples are disposed within the sample tube within the cutter; and  
a sample tube advancable within the hollow cutter, the sample tube having an open distal end sized for receiving a tissue sample severed by the hollow cutter the sample tube being releasably supported on the biopsy device such that the sample tube and at least one tissue sample stored therein may be removed from the biopsy device without disassembling the biopsy device.
2. (previously amended ) The biopsy device of Claim 1 wherein the sample tube is adapted to store multiple samples in an end to end configuration.
3. (original) The biopsy device of Claim 1 comprising a vacuum source in communication with the sample tube.
4. (original) The biopsy device of Claim 1 wherein the sample tube is advanced by fluid pressure.
5. (original) The biopsy device of Claim 1 wherein the sample tube is advanced pneumatically.

10/732,843  
END5007USNP

6. (original) The biopsy device of Claim 1 comprising a piston operatively associated with the sample tube.
7. (original) The biopsy device of Claim 1 comprising apparatus for advancing and retracting the cutter within the biopsy needle.
8. (previously amended) The biopsy device of Claim 7 comprising apparatus for advancing and retracting the sample tube within the cutter.
9. (original) The device of Claim 1 wherein the hollow needle comprises a lateral tissue receiving port spaced from the distal end of the needle.
10. (currently amended) The device of Claim 1 wherein the sample tube comprises a vacuum lumen and a sample lumen, and wherein the vacuum lumen extends along side of at least a portion of the sample lumen.
11. (original) The device of Claim 1 wherein the sample tube comprises a tube wall feature for retaining tissue samples.
12. (original) The device of Claim 11 wherein the tube wall feature comprises a notch disposed adjacent the distal end of the sample tube.
13. (original) The biopsy device of Claim 1 comprising a rotating journal for rotating and advancing the cutter.
14. (canceled)
15. (canceled)

10/732,843  
END5007USNP

16. (previously amended) A biopsy device comprising:  
a hollow biopsy needle having a lateral tissue receiving port;  
a hollow cutter advancable within the biopsy needle to sever tissue received within the tissue receiving port;  
a sample tube having an open distal end defining a distal opening, wherein the sample tube defines a central axis, wherein the distal opening defines a generally circular plane transverse to the sample tube, wherein the central axis intersects the plane, wherein the sample tube further comprises a proximal end in communication with a source of vacuum, the sample tube being releasably supported on the biopsy device, and the sample tube advancable within the cutter; and  
a drive mechanism for advancing and rotating the cutter within the biopsy needle, wherein the drive mechanism comprises an internally threaded, rotatably driven component for advancing and rotating the cutter.
17. (previously amended) A method of obtaining a tissue sample comprising the steps of:  
drawing tissue into a tissue receiving port of a hollow biopsy needle;  
advancing a hollow cutter in the needle to sever a tissue sample;  
advancing a hollow sample tube in the cutter to position the tissue sample in the sample tube, wherein the hollow sample tube has an open distal end, wherein the open distal end comprises a distally facing opening defined by the distalmost perimeter of the open distal end, wherein the tissue sample is axially received in the hollow sample tube through the opening at the open distal end of the hollow sample tube during the act of advancing the hollow sample tube.
18. (previously amended) The method of Claim 17 comprising stacking multiple samples within the sample tube in an end to end configuration.
19. (original) The method of Claim 17 comprising providing a vacuum through the sample tube.

10/732,843  
END5007USNP

20. (original) The method of Claim 17 comprising providing axial vacuum in the cutter with at least one sample disposed in the sample tube.